

## PureCloud Edge Standard v3 Technical Specifications

**Product Part No.: TH-900-PCEDGE-5140100**

<b>Platform</b>	HPE DL360 Gen10
<b>CPU</b>	Intel Xeon Silver 4000 series
<b>RAM</b>	32GB RAM
<b>Hard Drive(s)</b>	1TB SATA x 2
<b>Storage Controller</b>	HPE Smart Array Controller w/2GB flash backed write cache
<b>RAID Configuration</b>	RAID 1

### Server physical and operational specifications:

<b>Dimensions (HxWxD)</b>	4.29 x 43.46 x 74.98 cm (1.69 x 17.11 x 29.5 inches)
<b>Weight (approx.)</b>	16.78 kg (36.99 lbs)
<b>System Inlet Temperature</b>	10° to 35°C (50° to 95°F) at sea level with an altitude derating of 1.0°C per every 305 m (1.8°F per every 1000 ft) above sea level to a maximum of 3050 m (10,000 ft), no direct sustained sunlight. Maximum rate of change is 20°C/hr (36°F/hr).
<b>Relative Humidity</b>	Operating: 8% to 90% - Relative humidity (Rh), 28°C maximum wet bulb temperature, non-condensing. Non-Operating: 5 to 95% relative humidity (Rh), 38.7°C (101.7°F) maximum wet bulb temperature, non-condensing.
<b>Acoustic Noise</b>	Idle: 35dBA; Operating: 38dBA
<b>BTU Rating</b>	572.74 BTU / hr (at 115 VAC); 571.34 BTU/hr (at 240 VAC)
<b>Power Supply</b>	HPE 500W Flex Slot Platinum Hot Plug Low Halogen Power Supply x 2
<b>Power Requirement – Input (per power supply)</b>	100 to 120 VAC; 200 to 240 VAC 58-168 W @ 115 VAC / 59-168 W @ 240 VAC
<b>Network Adapter</b>	HPE Embedded Dual Port 361i Adapter
<b>Network Interface</b>	10Base-T/100Base-TX/1000Base-TX
<b>USB Interface</b>	1 x USB 3.0 (front) 2 x USB 3.0 (rear)
<b>Storage Drive Bay(s)</b>	2 x 3.5" SATA drive bay; user-replaceable drive in case of disk failure
<b>Rail Kit</b>	HPE 1U Gen9/10 LFF Easy Install Rail Kit
<b>Warranty</b>	3-year Advanced Product Replacement

Genesys may make changes to these specifications and product descriptions at any time, without notice.